



# DF1900

INDOOR DUAL SIDED KIOSK











Industrial grade IPS technology accurately displays image quality and colour depth with no fall-off in colour accuracy.



The 4K Ultra HD display delivers incredible image quality with four times resolution higher than Full HD.




These displays provide fantastic image quality with a remarkable viewing angle of 178° in both landscape and portrait.

#### 4. SCROLLING TEXT



You can display a "ticker tapy" style scrolling text message along the bottom of the screen.

#### 5. SURFACE PLASMA TREATMENT



The oleophobic coating makes the glass front more resistance to oil and water residue left by fingerprint marks and makes touch gestures smoother.

## 6. 10 POINT PCAP / IR TOUCH



Manipulate images, zoom in an out as well as perform many other touch gestures; Multiple users interacting with the screen at one time.





 $5w 8\Omega \times 2$ Integrated speakers

Integrated with two stereo speakers for audio element requirement.

## 8.FREE SCHEDULING SOFTWARE



Playlist can be scheduled for displaying different content at different times of the day.

#### 9.POWER TIMER



The screen can be set to automatic daily or weekly timing switches on and off.

# 10. 24/7 USAGE



The industrial grade panels are able to be in constant use 24/7 for over 60,000 hours.

## 11.ANDROID OR WINDOWS OS



Built-in Android 7.1 operating system and Windows 10 operating system options. You can also use your media player if required.

#### 12.NETWORK REMOTE CONTROL



LAN, Wi-Fi, 4G network connection are available. The playlist can be remotely updated over the internet.
















# PRODUCT SIZE

SIZE REFERENCE: **55 INCH** 







OTHER AVAILABLE SIZES: 43" 49" 55" 65" 75"

CONTENT MANAGEMENT DEVICE MANAGEMENT REMOTE CONTROL









- > The screens are fixed
- > Front and back is glass, the side is round arc aluminum profile

—DF1900—



- > A door can be opened
- > The screens are fixed
- ➤ The whole is made of steel plate and glass
  only in the screen area
- → Flat base

—DF2020—



- > Two doors can be opened
- ▶ Two screens can be moved and adjusted for easy maintenance
- > Front and back is glass, the side is flat aluminum profile
- ▶ Flat base













- CARTON BOX
- WOODEN CASE





FLIGHT CASE



# SPECIFICATIONS

ITEM	DETAILS	TECHNICAL PARAMETERS				
	Size	49inch	55inch	65inch	75inch	
	Display area (mm)	1084.8x610.2	1209.6x680.4	1428.48×803.52	1649.66×927.94	
	Resolution	1920x1080 / 3840x2160				
	Brightness	350 cd/m <sup>2</sup> / 500 cd/m <sup>2</sup> / 700 cd/m <sup>2</sup> / 1000 cd/m <sup>2</sup>				
Hardware data	Viewing angle	178° (H) / 178° (V)				
	Contrast ratio	1400:1				
	Shell material	aluminum profile, metal plate, tempered safety glass				
	Spearker	2X8Ω5W				
Power supply	Switch power	110-240VAC@ 50/60Hz				
Power consumption	Max Power consumption	60W	80W	100W	200W	

ITEM	DETAILS	TECHNICAL PARAMETERS 🔀		
	Motherboard	RK3288/ RK 3399		
	CPU	Cores:4; Basic frequency:1.8 GHz ,Cortex A17 / Dual Cortex-A72 big core+quad Cortex-A53 small core 64-bit CPU		
	Operating System	Android 5.1/ 7.1		
	Graphics	Integrated GPU ARM Mali-T764 / Quad core Arm mali-T860Mp4		
	Memory	2G		
Android version	Storage	16G		
	RJ45 LAN interface	100M/1000M		
	USB	4 USB 2.0 / 2 USB 3.0		
	Player Software	content management system		
	Audio support	Intergrated		
	Output interface	HDMI *1		
	Motherboard	H310		
	CPU	Intel i5 ≥6th generation(i3 & i7 for option)		
	Operating System	Windows 10 Pro		
	Graphics	Intel HD Graphics		
	Memory	4G RAM		
Windows version	Storage	120G SSD		
Williams reision	RJ45 LAN interface	100M/1000M		
	USB	USB*1, SD card*1		
	Player Software	To be specified by the client		
	Audio support	Intergrated		
	Output interface	HDMI*1, VGA*1		

DigitaITEM	DETAILS	TECHNICAL PARAMETERS
IGNAGE	Motherboard	SX-260
	CPU	HD video decoding chip
	Operating System	uCOS
	Memory	DDR 128MB
Standalone	Storage	NAND Flash 16G
version	Video format	MPEG1, MPEG2, MPEG4, H264, WMV
	USB	USB*1, SD card*1
	Input interface	HDMI*1,USB*1
20.45.452	USB	none
Driver board version	Audio support	PC audio, earphone input
Doard version	input interface	HDMI*1,VGA*1,DVI*1 / HDMI*1,DVI*1,VGA*1,DP*1
	Operating temperature	0°C ∼ +40°C
Application	Storage temperature	-20°C ∼ +60°C
Environment	Humidity	10-80% RH Non-condensing
	WiFi access point	Yes
Options	Cellular router	3G or 4G
Options	Touchscreen	capacitive touch
	LED backlit company logo	Yes







REMOTE TECHNICAL **SUPPORT** 



**IMPORTANT ACTIVITIES** 



FREE TECHNICAL **TRAINNING** 



VISIT VIP COUSTOMERS REGULARLY

